

5800 CONTROL VALVE



TESTED and CERTIFIED by the WQA to NSF/ANSI Std. 44 for material safety, structural integrity and performance, NSF/ANSI Std. 372 for low lead and CSA B483.1



UL listed to UL 979



TESTED EMC and Low Voltage Directive



Restriction of Hazardous Substance Compliant

FEATURES • BENEFITS

- Ⓡ Fiber-reinforced polymer valve body for superior strength and durability; non-corrosive, and UV-resistant
- Ⓡ Continuous service flow rate of 21 GPM with a backwash rate of 17 GPM
- Ⓡ Backwash capability accommodates softener tanks and filters up to 16" in diameter
- Ⓡ Fully adjustable 3- or 5-cycle control for efficient and reliable water treatment
- Ⓡ Time-tested, hydraulically-balanced piston for service and regeneration
- Ⓡ Optical sensor for precision cycle positioning
- Ⓡ Soft water refill for a cleaner brine tank
- Ⓢ Designed with double backwash for reduced hardness leakage
- Ⓢ Diagnostics for historical valve performance
- Ⓢ Programming stored in memory and will not be lost due to power outages

Remote Monitoring Technology

- Ⓢ WiFi connectivity allows user to view system status and receive push alerts (XTRi only)*

Sensor Technology

- Ⓢ Automatically adjusts to changing water hardness
- Ⓢ 24/7 monitoring ensures a continuous supply of quality water

CONFIGURATIONS • OPTIONS

- Ⓡ Time Clock, Meter, or Sensor initiated regeneration
- Ⓡ Filter or softener control valves
- Ⓡ Downflow co-current or upflow counter-current regeneration
- Ⓡ Plumbing connections in 3/4" or 1" NPT, BSP, and Sweat
- Ⓡ Fiber-reinforced polymer or stainless steel bypass valve
- Ⓡ Variable reserve or sensor technology options available for increased efficiency
- Ⓡ Programmable regeneration types for increased flexibility
- Ⓡ Three color bezel options of black, silver, or blue

TIMER OPTIONS

- Ⓢ **XTRi** - Premium touch screen LCD display with the ability to connect to Pentair Home and Pentair Pro apps via WiFi*

- Ⓡ **XTR2** - Premium touch screen LCD display with sensor capability and two programmable relay outputs for both normally opened and normally closed contacts
- Ⓡ **SXT** - Large LCD display with one programmable relay output for both normally open and normally closed contacts

* Please visit pentair.com/connectedsoftener for more information on Pentair Home and Pentair Pro apps.

VALVE SPECIFICATIONS

Valve Material	Fiber-reinforced polymer
Inlet/Outlet	3/4" or 1" NPT, BSP, Sweat
Cycles	5

FLOW RATES (50 PSI INLET) – VALVE ALONE

Continuous 15 psi	21 GPM (4.8 m ³ /h)
Peak 25 psi (1.7 bar) drop Cv	27 GPM (6.1 m ³ /h)
flow at 1 psi	5.4
Max. Backwash 25 psi (1.7 bar) drop	17 GPM (3.9 m ³ /h)

REGENERATION

Downflow/Upflow	Both
Adjustable Cycles	Yes
Timers Available	
XTR2/XTRi:	0 - 240 min/cycle
SXT:	0 - 199 min/cycle

METER INFORMATION

Meter Accuracy	
3/4" Paddle/Turbine:	0.25 - 15 GPM ± 5% (0.06 - 3 m ³ /h)
Meter Capacity Range	
XTR2/XTRi:	1 - 9,999,999 gal (0 - 378,541 m ³)
SXT:	1 - 999,900 gal (0 - 3,785 m ³)

DIMENSIONS

Distributor Pilot	1.05" O.D. (26.7 mm)
Drain Line	1/2" NPTF Quick-Connect
Brine Valve 1600:	3/8" 1610
Injector System	2.5" - 8 NPSM
Mounting Base	9" (228 mm)
Height from Top of Tank	
Riser Tube Diameter	3/4" (19 mm)
Riser Height	1/4" below top of tank

TYPICAL APPLICATIONS

Water Softener	6 - 16" Diameter 8 - 16" Diameter based on 10 GPM/ft ²
Filters	

ADDITIONAL INFORMATION

Electrical Rating	12 Volts DC
Estimated Shipping Weight	
Time Clock:	7 lbs (3.17 kg)
Metered Valve:	10 lbs (4.53 kg)
Pressure	
Hydrostatic:	300 psi (20 bar)
Working:	20 - 125 psi (1.4 - 8.5 bar)
Temperature	
Cold Water Valve:	34 - 110°F (1 - 43°C)

Authorized distributor

Aquality Intelligent Solutions Pvt. Ltd



8-1-284/OU/566, 2nd Floor, OU Colony, Shaikpet, Hyderabad,
Telangana, India, 500008

+91 70938 98486 | sales@aquality.in | aquality.co.in



13845 Bishops Dr. | Suite 200 | Brookfield, WI 53005 | United States
P: 262.238.4400 | Customer Service: 800.279.9404 | tech-support@pentair.com | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

© 2023 Pentair. All rights reserved.

4005571 JL23