

TECHNICAL SHEET

FLECK
COMMERCIAL VALVE 5810



TECHNICAL SHEET

OUR
WEBSITE



FLECK 5810 COMMERCIAL VALVE

TECHNICAL CHARACTERISTICS

- Fiber-reinforced polymer valve body
- Continuous service flow rate of 8.2 m³/h (36 GPM) with a backwash of 6.3 m³/h (28 GPM)
- Backwash capability accommodates softener tanks up to 21 inches and filters up to 21 inches in diameter
- Fully adjustable 3- or 5-cycle control
- Time-tested, hydraulically-balanced piston
- Optical sensor
- Soft water refill
- Variable brining when used with XTR timer
- Diagnostics
- Programming stored in memory



OPTIONS

- Filter or softener control valves
- Downflow co-current or upflow counter-current regeneration
- Plumbing connections in 1 and 1.25 inches BSP
- Fiber-reinforced polymer high-flow bypass valve
- Variable brining when used with XTR timer
- Programmable regeneration types
- Two color bezel options black or blue
- **XTR/Hurricane**- Premium touch screen LCD display with two programmable relay outputs for both normally opened and normally closed contacts
- **SXT/Typhoon**- Large LCD display and user-selectable time clock or metered function; usable for filtration and softener systems



VALVE SPECIFICATIONS

Valve material	Fiber - reinforced polymer
Inlet/Outlet	1 or 1.25 inch BSP
Cycles	5

FLOW RATE (3.5 BAR INLET) – VALVE ALONE

	Downflow m ³ /h (GPM)	Upflow m ³ /h (GPM)	Filter m ³ /h (GPM)
Continuous ($\Delta p = 1$ bar)	8.2 (36)	7.9 (39)	7.0 (31)
Peak ($\Delta p = 1.8$ bar)	10.6 (47)	10.1 (45)	9.0 (40)
Kv*	8.1	7.7	6.9
Cv**	9.4	8.9	8.0
Max. backwash ($\Delta p = 1.7$ bar)	6.3 (28)	6.9 (30)	7.5 (33)

* Kv: Service flow rate (valve alone) in m³/h at 1 bar pressure drop, water temperature of 16°C.
 **Cv : Service flow rate (valve alone) in gpm at 1PSI pressure drop at water temperature of 60°F

REGENERATION

Downflow / Upflow	Both
Adjustable cycles	Yes
Time available	Typhoon (SXT): 0 - 199 min/cycle Hurricane (XTR): 0 - 240 min/cycle

METER INFORMATION

Meter accuracy	1.25-inch turbine: 0.45 - 9 m ³ /h (2 - 40 GPM \pm 5%)
----------------	---------------------------------------------------------------------

DIMENSIONS

Distributor pilot	26.7 mm (1.05 inch) O.D
Drain line	0.75 or 1 inch BSP
Injector brine system	1600: 3/8"
Mounting base	2.5 inches - 8 NPSM
Height from top of tank	287 mm (11.3 inches)
Riser height	0.25 inches below top of tank

TYPICAL APPLICATIONS

Water softener	8 - 21 inches Ø
Filter	8 - 21 inches Ø (based on 24,5 m ³ /h - 10 GPM/ft ²)

ADDITIONAL INFORMATION

Electrical rating	12 V DC
Pressure	Hydrostatic: 20 bar (300 psi) Working: 1.4 - 8.5 bar (20 - 125 psi)
Temperature	Cold water valve: 1 - 43°C (34 - 110°F)
Estimated Shipping Weight	5 kg

Authorized distributor
Aquality Intelligent Solutions Pvt. Ltd



8-1-284/OU/566, 2nd Floor , OU Colony, Shaikpet, Hyderabad,
Telangana, India, 500008

+91 70938 98486 | sales@aquality.in | aquality.co.in



WATER QUALITY SYSTEMS

EVERPURE-SHURFLO WORLD HEADQUARTERS, 1040 MUIRFIELD DRIVE, HANOVER PARK, IL 60133 USA • WWW.EVERPURE.COM

800.942.1153 MAIN (US ONLY) • 630.307.3000 MAIN • 630.307.3030 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO AUSTRALIA / NEW ZEALAND, 1-21 MONASH DRIVE, DANDENONG SOUTH, VIC 3175 AUSTRALIA

1300 576 190 TEL • AU.EVERPURE@PENTAIR.COM EMAIL

EVERPURE-SHURFLO SOUTHEAST ASIA,

390 HAVELOCK ROAD , #04-01 KING'S CENTRE, SINGAPORE 169662

65.6768 5800 TEL • 65. 6737 5149 FAX • CSEVERPURE@PENTAIR.COM EMAIL

EVERPURE CHINA • 21F CLOUD 9 PLAZA, NO 1118, SHANGHAI, 200052, CHINA

TEL 86 21 3211 4588 • FAX 86 21 3211 4583

www.everpure.com www.everpurechina.com.cn

Hotline: 400-921-7015 (China Mainland Only)

E-mail: China.Water@Pentair.com

EV-FS001 © 2015 Pentair Filtration Solutions, LLC. All Rights Reserved.

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.
© 2021 Pentair. All rights reserved.